

FT »


# PALAO'S DESIGN NARROW FRAME

## TECHNICAL DATA



	220-240 50 Hz	PF > 0.95	IP40	CRI >80	IK07	1-10V/DALI Optional
---	------------------	--------------	------	------------	------	------------------------

State of the art LED panel having only 4mm width frame, overshadow your competitor's panels by attractive and neat looking; be able to connect one by one into different shapes, diversified installation way, low glare rating UGR<19, PMMA LGP, anti yellowing.

DRIVER CC, 900mA, 27-55 Vdc	Standard	Lighting Control Phase Dim.   1-10V   DALI		
CRI	Standard	CRI >80	CRI >90	CRI >97
BEAM ANGLE				
FINISH	White (WH)			

### TECHNICAL DATA

LED	: BRIDGELUX SMD LED
System Power	: 36 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 100 lm/W (@4000K)
Lifetime	: L <sub>80</sub> B <sub>10</sub> 50,000Hrs, Ta@35°C
UGR	: <22

### GENERAL

Mounting	: Ceiling Recessed, Indoor
Housing	: Extruded aluminium body
Heatsink	: Aluminium
Diffuser	: PMMA
Adjustability	: No
Driver Mounting	: Remote
Emergency kit	: Optional

IP Rating	: IP40
IK Rating	: IK07
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 55°C
Glow-wire test	: 650°
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K 6000K

FT »

# PALAOS DESIGN NARROW FRAME

## TECHNICAL DATA



### PALAOS DESIGN NARROW FRAME

DIMENSIONS	COLOR TEMP.	POWER	LUMENS	CODE
595 W x 595 L x 16.7 H	4000K	36 W	3350 lm	INT13175
595 W x 595 L x 16.7 H	5000K		3600 lm	INT13176
295 W x 1195 L x 16.7 H	4000K		3350 lm	INT13177

3000K 4000K 5000K 6000K

#### NOTES

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

[www.switch-made.com](http://www.switch-made.com)

Updated on February 28, 2019

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.