



FT







AERO 60

TECHNICAL DATA



	200-240 Vac	IP20	CREE COB LED	CRI > 80 / > 90	< 3SDCM	DIMMABLE 0-10V/DALI
---	-------------	------	--------------	-----------------	---------	------------------------

Multi COB designed powerful LED downlight, with most efficient and powerful LED chip with luminous efficiency, stable performance to provide uniform and comfort lighting distribution, high quality aluminium body and heat sink to ensure an ingenious shape and a sufficient dissipation space for thermal management, remote driver, best suitable for high ceiling applications such as auditoriums, concert halls, airport.

DRIVER	Lighting Control			
	Standard	Phase Dim.	1-10V	DALI
CRI	Standard			
	CRI > 80	CRI > 90	CRI > 97	
BEAM ANGLE				
	15°	24°	38°	60°
FINISH	<i>White (WH)</i> <i>Grey (GY)</i> <i>Black (BK)</i>			
				

TECHNICAL DATA

LED	: CREE 1507
System Power	: 60 W
MacAdam Step	: SDCM < 2
Luminaire Efficacy	: 85 lm/W (@5000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@25°C
UGR	: < 19

GENERAL

Mounting	: Ceiling recessed, Indoor
Housing	: Die-cast Aluminium
Heatsink	: Aluminium
Diffuser	: Tempered Glass
Adjustability	: Yes
Driver Mounting	: Remote
Emergency kit	: Optional

IP Rating	: IP20
IK Rating	: IK07
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 55°C
Glow-wire test	: 650°
Weight	: - Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K


AERO 60

CREE 1507 LED



Color Temp.	Power	Lumens	Code
3000K	60 W	5144 lm	INT05134-30K
4000K		5415 lm	INT05134-40K
5000K		5100 lm	INT05134-50K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	