



FT



B-TUBE-I 20

TECHNICAL DATA



	220-240 Vac	IP65	IK08	CRI >80	CREE COB LED
---	----------------	------	------	------------	-----------------

Durable, high sturdiness and robust wall mounted luminaire, outstanding feature of this range is the option to have with 316L stainless steel mirror finish, with one directional or two directional options, wide choice of beam optics, extruded aluminum and die-cast aluminium housing, outdoor UV resistant powder coat finishing, 316L SS screws, fire resistant silicone seal waterproof gasket, 8mm thick toughened flush glass with trim, integrated driver, optional square version and 60W model also available.


DRIVER
CC, 500mA, 32-42vdc

Lighting Control
Standard

CRI

Standard
CRI >80 CRI >90 CRI >95

BEAM ANGLE



FINISH

White (WH) RAL9016 Grey (GY) RAL9006 Black (BK) RAL9005

TECHNICAL DATA

LED	: CREE CXA2520
System Power	: 20 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 93 lm/W (@5000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@25°C
UGR	: -

GENERAL

Mounting	: Wall mounted, Outdoor
Housing	: Extruded and die-cast aluminium body
Reflector	: Aluminium
Diffuser	: Toughened glass (8mm thick)
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP65
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -20° to 60°C
Glow-wire test	: 650°
Weight	: 3.00 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.


B-TUBE-I 20



COLOR TEMP.	POWER	LUMENS	CODE
3000K	20 W	1758 lm	EXT05119
4000K		1820 lm	EXT05120

3000K 4000K 5000K

DIMENSION

FINISH
(Optional)

316L SS
MIRROR FINISH



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT
LUMINAIRE REF.
QUANTITY
DATE

Contact Name
Mobile
Email