



FT



BETA 20 SUSPENDED

TECHNICAL DATA



	100-240 Vac	IP20	<3SDCM	CRI >80	CREE 1512 COB LED
---	----------------	------	--------	------------	----------------------

BETA pendant range combines the unique design style and compact structure with wide choice of power series and dedicated optic choices, suit for accent lighting and general lighting, stable performance to provide uniform and comfortable lighting level, high visual comfort, tensile aluminium body with oxidation treatment provides corrosion resistances, built-in driver, delivered with round ceiling base, optional wattages of 8W/12W/25W also available.

DRIVER	Lighting Control Standard
CRI	Standard CRI >80 CRI >90
BEAM ANGLE	
BODY FINISH	White (WH) Grey (GY) Black (BK)
REFLECTOR FINISH	Gold High Gloss Black High Gloss Silver Frosted

TECHNICAL DATA

LED	: CREE 1502
System Power	: 20 W
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 93 lm/W (@4000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@35°C
UGR	: <19

GENERAL

Mounting	: Suspended, Indoor
Housing	: Die-cast aluminium
Reflector	: Aluminium
Diffuser	: PMMA
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP20
IK Rating	: IK04
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.

The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

BETA 20 SUSPENDED

TECHNICAL DATA




BETA 20 SUSPENDED



COLOR TEMP.	POWER	LUMENS	CODE
2700K	20 W	1700 lm	INT07343-27K
3000K		1780 lm	INT07343-30K
4000K		1860 lm	INT07343-40K

2700K 3000K 4000K 5000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 13, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.