



FT »

BETA 20 TRACK

TECHNICAL DATA

	100-240 Vac	IP20	<3SDCM	CRI >80	100lm/W	CREE COB LED
---	----------------	------	--------	------------	---------	-----------------

BETA range offers stylish and compact solution with excellent modular combination concept in different applications and mounting possibilities, suit for accent lighting and general lighting, stable performance to provide uniform and comfortable lighting level, aluminium body with oxidation treatment provides corrosion resistances, integrated driver, also available in 15W/25W version.

DRIVER | Lighting Control
Standard

CRI | Standard
CRI >80 CRI >90

BEAM ANGLE | 

BODY FINISH | White (WH) Black (BK)

TECHNICAL DATA

LED : CREE 1502
System Power : 20 W
MacAdam Step : <3 SDCM
Luminaire Efficacy : 99 lm/W (@4000K)
Lifetime : L₈₀ B₁₀ 50,000Hrs, Ta@35°C
UGR : <19

GENERAL

Mounting : Suspended, Indoor
Housing : Die-cast aluminium
Reflector : Aluminium
Diffuser : PMMA
Adjustability : No
Driver Mounting : Integrated
Emergency kit : Not available

IP Rating : IP20
IK Rating : IK04
Protection Class IEC : II
Energy Class : A+
Working Temp. : -20° to 50°C
Glow-wire test : 650°C
Weight : -
Warranty : 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K

FT »

BETA 20 TRACK

TECHNICAL DATA




BETA 20 TRACK



COLOR TEMP.	POWER	LUMENS	CODE
2700K	20 W	1800 lm	INT03014-27K
3000K		1920 lm	INT03014-30K
4000K		1980 lm	INT03014-40K

2700K 3000K 4000K 5000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 21, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.