



FT »

BETA 30 TRACK

TECHNICAL DATA

	100-240 Vac	IP20	<3SDCM	CRI >80	100lm/W	CREE COB LED
---	-------------	------	--------	---------	---------	--------------

BETA range offers stylish and compact solution with excellent modular combination concept in different applications and mounting possibilities, suit for accent lighting and general lighting, stable performance to provide uniform and comfortable lighting level, aluminium body with oxidation treatment provides corrosion resistances, integrated driver, also available in 15W/25W version.

DRIVER	Lighting Control Standard
CRI	Standard CRI >80 CRI >90
BEAM ANGLE	
BODY FINISH	White (WH) Black (BK) 

TECHNICAL DATA

LED	: CREE 1502
System Power	: 30 W
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 99 lm/W (@4000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@35°C
UGR	: <19

GENERAL

Mounting	: Suspended, Indoor
Housing	: Die-cast aluminium
Reflector	: Aluminium
Diffuser	: PMMA
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP20
IK Rating	: IK04
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K

FT »

BETA 30 TRACK

TECHNICAL DATA




BETA 30 TRACK



COLOR TEMP.	POWER	LUMENS	CODE
2700K	30 W	2550 lm	INT03017-27K
3000K		2670 lm	INT03017-30K
4000K		2880 lm	INT03017-40K

2700K 3000K 4000K 5000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	



www.switch-made.com

Updated on May 9, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.