



FT



## BETA 20 CEILING MOUNTED

### TECHNICAL DATA



	100-240 Vac	IP20	<3SDCM	CRI >80	CREE COB LED
---	-------------	------	--------	---------	--------------

BETA range offers stylish and compact solution with excellent modular combination concept in different applications and mounting possibilities, anti-glare design, suitable for accent lighting and general lighting, stable performance to provide uniform and comfortable lighting level, aluminium body with oxidation treatment provides corrosion resistances, reliable and efficient installation, integrated driver.

DRIVER	Lighting Control Standard
CRI	Standard CRI >80 CRI >90
BEAM ANGLE	15° 30° 45°
BODY FINISH	White (WH) Grey (GY) Black (BK)
REFLECTOR FINISH	Gold High Gloss Black High Gloss Silver Frosted

#### TECHNICAL DATA

LED	: CREE 1502
System Power	: 20 W
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 93 lm/W (@4000K)
Lifetime	: L <sub>80</sub> B <sub>10</sub> 50,000Hrs, Ta@35°C
UGR	: <19

#### GENERAL

Mounting	: Ceiling mounted, Indoor
Housing	: Die-cast aluminium
Reflector	: Aluminium
Diffuser	: PMMA
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP20
IK Rating	: IK04
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K



[www.switch-made.com](http://www.switch-made.com)

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

# BETA 20 CEILING MOUNTED

## TECHNICAL DATA




### BETA 20 CEILING MOUNTED



COLOR TEMP.	POWER	LUMENS	CODE
2700K	20 W	1720 lm	INT07322-27K
3000K		1800 lm	INT07322-30K
4000K		1860 lm	INT07322-40K

2700K 3000K 4000K 5000K

DIMENSION



### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 13, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.