



FT



## BETA 8 CEILING MOUNTED

### TECHNICAL DATA



|   |             |      |        |         |              |
|---|-------------|------|--------|---------|--------------|
|  | 100-240 Vac | IP20 | <3SDCM | CRI >80 | CREE COB LED |
|---|-------------|------|--------|---------|--------------|

BETA range offers stylish and compact solution with excellent modular combination concept in different applications and mounting possibilities, anti-glare design, suitable for accent lighting and general lighting, stable performance to provide uniform and comfortable lighting level, aluminium body with oxidation treatment provides corrosion resistances, reliable and efficient installation, integrated driver.


DRIVER  
CC, 200mA, 27-45 Vdc

Lighting Control  
Standard

CRI

Standard  
CRI >80 CRI >90

BEAM ANGLE



BODY FINISH

White (WH) Grey (GY) Black (BK)

REFLECTOR FINISH



#### TECHNICAL DATA

|                    |  |
|--------------------|--|
| LED                | : CREE 1507  |
| System Power       | : 8 W  |
| MacAdam Step       | : <3 SDCM  |
| Luminaire Efficacy | : 93 lm/W (@4000K)                                   |
| Lifetime           | : L <sub>80</sub> B <sub>10</sub> 50,000Hrs, Ta@35°C |
| UGR                | : <19  |

#### GENERAL

|                 |                           |
|-----------------|---------------------------|
| Mounting        | : Ceiling mounted, Indoor |
| Housing         | : Die-cast aluminium      |
| Reflector       | : Aluminium               |
| Diffuser        | : PMMA                    |
| Adjustability   | : No                      |
| Driver Mounting | : Integrated              |
| Emergency kit   | : Not available           |

|                      |                               |
|----------------------|-------------------------------|
| IP Rating            | : IP20                        |
| IK Rating            | : IK04                        |
| Protection Class IEC | : II                          |
| Energy Class         | : A+                          |
| Working Temp.        | : -20° to 50°C                |
| Glow-wire test       | : 650°C                       |
| Weight               | : -                           |
| Warranty             | : 3 yrs (extendable to 5 yrs) |

2700K 3000K 4000K 5000K



[www.switch-made.com](http://www.switch-made.com)

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

# BETA 8 CEILING MOUNTED

## TECHNICAL DATA




### BETA 8 CEILING MOUNTED



| COLOR TEMP. | POWER | LUMENS | CODE         |
|-------------|-------|--------|--------------|
| 2700K       | 8 W   | 680 lm | INT07316-27K |
| 3000K       |       | 712 lm | INT07316-30K |
| 4000K       |       | 744 lm | INT07316-40K |

2700K 3000K 4000K 5000K

DIMENSION



### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

|                |  |
|----------------|--|
| PROJECT        |  |
| LUMINAIRE REF. |  |
| QUANTITY       |  |
| DATE           |  |
| Contact Name   |  |
| Mobile         |  |
| Email          |  |

www.switch-made.com

Updated on April 13, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.