



FT »

BLACKMOON 14 SUSPENDED

TECHNICAL DATA




	220-240V 50-60Hz	IP20	UGR <19	CRI >80/>90/>97	CITIZEN 1202 LED
---	---------------------	------	------------	--------------------	---------------------

High-end innovative compact LED light for accentuation lighting application, specially designed qualitative-smoothly curved reflector ensure better visual comfort with an optimum light output ratio, excellent glare control, high efficient LED COB, SDCM<2, machined aluminium trim with powder-coated finishing, die-cast aluminium heat sink with sand black finishing, high reflectance aluminium reflector, optional 10W model also available.

DRIVER | Lighting Control
Standard

CRI |   

BEAM ANGLE



TECHNICAL DATA

LED : CITIZEN 1202 COB
System Power : 14 W
MacAdam Step : <2 SDCM
Luminaire Efficacy : 90 lm/W (@4000K)
Lifetime : L₇₀ B₅₀ 50,000Hrs, Ta@35°C
UGR : <19

GENERAL

Mounting : Suspended, Indoor
Housing : Die-cast aluminium
Reflector : Aluminium
Diffuser : Clear glass
Adjustability : No
Driver mounting : Integrated
Emergency kit : N.A.

IP Rating : IP20
IK Rating : 04
Protection Class IEC : II
Energy Class : A+
Working Temp. : -20° to 50°C
Glow-wire test : 960°C
Weight : 0.55 Kg.
Warranty : 3 yrs (extendable to 5 yrs)

COLOR TEMP.	POWER	CRI	LUMENS	CODE
2700K	14 W	90+	1280 lm	INT03024-27K
3000K			1300 lm	INT03024-30K
4000K			1350 lm	INT03024-40K

FT



BLACKMOON 14 SUSPENDED

TECHNICAL DATA


FINISH

Body:


White (WH) - Black (BK)

Reflector:

High Gloss Black (HGB) - High Gloss Silver (HGS) - Frosted Silver (FS) - White (WH) - Gold (GD) - Black (BK)



DIMENSION



NOTES

Project	
Luminaire Ref.	
Quantity	
Date	
Contact Name	
Mobile	
Email	

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS



www.switch-made.com

Updated on April 22, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.