



FT

BLACKMOON 20 SUSPENDED

TECHNICAL DATA




	220-240V 50-60Hz	IP20	UGR <19	CRI >80/>90/>97	CITIZEN 1204 LED
---	---------------------	------	------------	--------------------	---------------------

High-end innovative compact LED light for accentuation lighting application, specially designed qualitative-smoothly curved reflector ensure better visual comfort with an optimum light output ratio, excellent glare control, high efficient LED COB, SDCM<2, machined aluminium trim with powder-coated finishing, die-cast aluminium heat sink with sand black finishing, high reflectance aluminium reflector, optional 10W model also available.

DRIVER | Lighting Control
Standard

CRI |   

BEAM ANGLE



TECHNICAL DATA

LED : CITIZEN 1204 COB
System Power : 20 W
MacAdam Step : <2 SDCM
Luminaire Efficacy : 90 lm/W (@4000K)
Lifetime : L₇₀ B₅₀ 50,000Hrs, Ta@35°C
UGR : <19

GENERAL

Mounting : Suspended, Indoor
Housing : Die-cast aluminium
Reflector : Aluminium
Diffuser : Clear glass
Adjustability : No
Driver mounting : Integrated
Emergency kit : N.A.

IP Rating : IP20
IK Rating : 04
Protection Class IEC : II
Energy Class : A+
Working Temp. : -20° to 50°C
Glow-wire test : 960°C
Weight : 0.55 Kg.
Warranty : 3 yrs (extendable to 5 yrs)

COLOR TEMP.	POWER	CRI	LUMENS	CODE
2700K	20 W	90+	1674 lm	INT03025-27K
3000K			1700 lm	INT03025-30K
4000K			1751 lm	INT03025-40K

Body:

White (WH) - Black (BK)



Reflector:

High Gloss Black (HGB) - High Gloss Silver (HGS) - Frosted Silver (FS) - White (WH) - Gold (GD) - Black (BK)



Technical drawing of a vertical rod with a cap and a break. The rod has a diameter of 75 mm. The distance from the cap to the start of the break is 1200 mm. The distance from the start of the break to the bottom of the rod is 140 mm.

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

Project	
Luminaire Ref.	
Quantity	
Date	
Contact Name	
Mobile	
Email	