



FT »

## BLACKMOON 10 SUSPENDED

### TECHNICAL DATA




	220-240V 50-60Hz	IP20	UGR <19	CRI >80/>90/>97	CITIZEN 1202 LED
---	---------------------	------	------------	--------------------	---------------------

High-end innovative compact LED light for accentuation lighting application, specially designed qualitative-smoothly curved reflector ensure better visual comfort with an optimum light output ratio, excellent glare control, high efficient LED COB, SDCM<2, machined aluminium trim with powder-coated finishing, die-cast aluminium heat sink with sand black finishing, high reflectance aluminium reflector, optional 10W model also available.

DRIVER | Lighting Control  
Standard

CRI |   

BEAM ANGLE



#### TECHNICAL DATA

LED : CITIZEN 1202 COB  
System Power : 10 W  
MacAdam Step : <2 SDCM  
Luminaire Efficacy : 90 lm/W (@4000K)  
Lifetime : L<sub>70</sub> B<sub>50</sub> 50,000Hrs, Ta@35°C  
UGR : <19

#### GENERAL

Mounting : Suspended, Indoor  
Housing : Die-cast aluminium  
Reflector : Aluminium  
Diffuser : Clear glass  
Adjustability : No  
Driver mounting : Integrated  
Emergency kit : N.A.

IP Rating : IP20  
IK Rating : 04  
Protection Class IEC : II  
Energy Class : A+  
Working Temp. : -20° to 50°C  
Glow-wire test : 960°C  
Weight : - Kg.  
Warranty : 3 yrs (extendable to 5 yrs)

COLOR TEMP.	POWER	LUMENS	CODE
2700K	10 W	886 lm	INT03113-27K
3000K		900 lm	INT03113-30K
4000K		927 lm	INT03113-40K



[www.switch-made.com](http://www.switch-made.com)

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

\_\_\_\_\_



CE RoHS

[illegible]