



FT »

BLACKMOON 8 TRACK

TECHNICAL DATA



	220-240V 50-60Hz	IP20	UGR <19	CRI >80/>90/>97	CITIZEN 1202 LED
---	---------------------	------	------------	--------------------	---------------------

High-end innovative compact LED track light for accentuation lighting application, specially designed qualitative-smoothly curved reflector ensure better visual comfort with an optimum light output ratio, excellent glare control, high efficient LED COB offering >95 lm/W, SDCM<2, machined aluminium trim with powder-coated finishing, die-cast aluminium heat sink with sand black finishing, high reflectance aluminium reflector, optional 10W/14W model also available.

DRIVER | Lighting Control
Standard

CRI | CRI >80 | Standard CRI >90 | CRI >97

BEAM ANGLE |  | 

TECHNICAL DATA

LED : CITIZEN 1202 COB
System Power : 8 W
MacAdam Step : <2 SDCM
Luminaire Efficacy : 90 lm/W (@4000K)
Lifetime : L₇₀ B₅₀ 50,000Hrs, Ta@35°C
UGR : <19

GENERAL

Mounting : Track Mounting, Indoor
Housing : Die-cast aluminium
Reflector : Aluminium
Diffuser : Clear glass
Adjustability : Yes
Driver mounting : Track adapter
Emergency kit : N.A.

IP Rating : IP20
IK Rating :
Protection Class IEC : II
Energy Class : A+
Working Temp. : -20° to 50°C
Glow-wire test : 960°C
Weight :
Warranty : 3 yrs (extendable to 5 yrs)

COLOR TEMP.	POWER	CRI	LUMENS	CODE
2700K	8 W	90+	704 lm	INT03023-27K
3000K			712 lm	INT03023-30K
4000K			740 lm	INT03023-40K

FT »

BLACKMOON 8 TRACK

TECHNICAL DATA

FINISH

Body:

White (WH) - Black (BK)




Reflector:

High Gloss Black (HGB) - High Gloss Silver (HGS) - Frosted Silver (FS) - White (WH) - Gold (GD) - Black (BK)



DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

Project	
Luminaire Ref.	
Quantity	
Date	
Contact Name	
Mobile	
Email	