

FT



## BLACKMOON 10 II-S CEILING MOUNTED

### TECHNICAL DATA



	220-240V 50-60Hz	IP20	UGR <19	CRI >80/>90/>97	CITIZEN LED CLU028-1202	DIMMABLE 1-10V/DALI Optional
---	---------------------	------	------------	--------------------	----------------------------	------------------------------------

High-end innovative compact LED surface downlight for accentuation lighting application, specially designed qualitative-smoothly curved reflector ensure better visual comfort with an optimum light output ratio, excellent glare control, high efficient LED COB offering >90 lm/W, SDCM<2, machined aluminium trim with powder-coated finishing, die-cast aluminium heat sink with sand black finishing, high reflectance aluminium reflector.


DRIVER  
CC, 250mA, 34Vdc

Lighting Control  
Standard ☐ Phase Dim. ☐ 1-10V ☐ DALI ☐

CRI

Standard  
☐ CRI >80 ☐ CRI >90 ☐ CRI >97

BEAM ANGLE



#### TECHNICAL DATA

LED	: CITIZEN CLU028-1202 COB
System Power	: 2 x 10 W
MacAdam Step	: <2 SDCM
Luminaire Efficacy	: 80 lm/W (@3000K)
Lifetime	: L <sub>70</sub> B <sub>50</sub> 50,000Hrs, Ta@35°C
UGR	: <19

#### GENERAL

Mounting	: Ceiling Mounted, Indoor
Housing	: Die-cast aluminium
Reflector	: Aluminium
Diffuser	: Clear glass
Adjustability	: Yes (355° +30°V)
Driver mounting	: Integrated
Emergency kit	: N.A.

IP Rating	: IP20
IK Rating	: -
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 960°C
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

COLOR TEMP.	POWER	CRI	LUMENS	CODE
2700K	2 x 10 W	90+	2 x 886 lm	INT03107-27K
3000K			2 x 900 lm	INT03107-30K
4000K			2 x 927 lm	INT03107-40K



[www.switch-made.com](http://www.switch-made.com)

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT

# BLACKMOON 10 II-S CEILING MOUNTED



## TECHNICAL DATA

FINISH


### Trim:

White (WH) - Black (BK)



### Reflector:

High Gloss Black (HGB) - High Gloss Silver (HGS) - Frosted Silver (FS) - White (WH)



BK-HGB



WH-FS




BK-BK



WH-BK

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	

Contact Name	
Mobile	
Email	