



FT » BLACKMOON 10 TRACK

TECHNICAL DATA



	220-240V 50-60Hz	IP20	UGR <19	CRI >80/>90/>97	CITIZEN LED CLU028-1204	DIMMABLE 1-10V/DALI Optional
---	---------------------	------	------------	--------------------	----------------------------	------------------------------------

High-end innovative compact LED tracklight for accentuation lighting application, specially designed qualitative-smoothly curved reflector ensure better visual comfort with an optimum light output ratio, excellent glare control, high efficient LED COB offering >90 lm/W, SDCM<2, machined aluminium trim with powder-coated finishing, die-cast aluminium heat sink, high reflectance aluminium reflector.

DRIVER	Lighting Control
	Standard <input type="checkbox"/> Phase Dim. <input type="checkbox"/> DALI <input type="checkbox"/>
CRI	CRI >80 <input type="checkbox"/> Standard CRI >90 <input type="checkbox"/> CRI >97 <input type="checkbox"/>
BEAM ANGLE	 

TECHNICAL DATA

LED	: CITIZEN CLU028-1204 COB
MacAdam Step	: <2 SDCM
Luminaire Efficacy	: 90 lm/W (@4000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <19

GENERAL

Mounting	: Track Mounted, Indoor
Housing	: Die-cast aluminium
Reflector	: Aluminium
Diffuser	: Clear glass
Adjustability	: Yes (365°H + 90°V)
Driver mounting	: Adaptor
Emergency kit	: NA
IP Rating	: IP20
IK Rating	: II
Protection Class IEC	: II
Energy Class	: A++
Working Temp.	: -20° to 50°C
Glow-wire test	: 960°C
Weight	: 3 yrs (extendable to 5 yrs)
Warranty	: 3 yrs (extendable to 5 yrs)

COLOR TEMP.	POWER	CRI	LUMENS	CODE
2700K	10 W	90+	886 lm	INT03109-27K
3000K			900 lm	INT03109-30K
4000K			927 lm	INT03109-40K

FT



BLACKMOON 10 TRACK

TECHNICAL DATA

FINISH

Body:

White (WH) - Black (BK)



Reflector:

High Gloss Black (HGB) - High Gloss Silver (HGS) - Frosted Silver (FS) - White (WH) - Gold (GD) - Sand Black (SB)



WH-BK



WH-WH



BK-BK





BK-WH



BK-SB

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT
LUMINAIRE REF.
QUANTITY
DATE

Contact Name

Mobile

Email



www.switch-made.com

Updated on April 21, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.