


FT »


BOBI 30

TECHNICAL DATA



	220-240 Vac	IP65	IK08	CRI >80	PF >0.9
---	-------------	------	------	---------	---------

Discreet and elegantly designed bollard for urban landscape, compact and slim body construction, with two-sided diffused light emission on narrow slit openings, uniform and precise lighting distribution with high visual comfort, good glare reduction, tough housing of die-cast aluminium, opal anti-UV diffuser, corrosion resistant, powder coat finish for extreme outdoor environments, longer life span, integrated driver.

DRIVER	Lighting Control Standard
CRI	Standard CRI >80
BEAM ANGLE	 120°
FINISH	Grey (GY) Black (BK)

TECHNICAL DATA

LED	: SMD LED
System Power	: 30 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 50 lm/W (@4000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@35°C
UGR	: -

GENERAL

Mounting	: Surface mounted, Outdoor
Housing	: Die-cast aluminium
Heatsink	: Aluminium
Diffuser	: Tempered glass
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: NA

IP Rating	: IP65
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A+
Working Temp.	: -20° to 55°C
Glow-wire test	: 850°
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K 6500K

FT »

BOBI 30

TECHNICAL DATA



BOBI 30 L600



BOBI 30 L900



LENGTH	COLOR TEMP.	POWER	LUMENS	CODE
L600	4000 K	2 x 15 W	2 x 985 lm	EXT19062-40K
	3000 K	2 x 15 W	2 x 930 lm	EXT19062-30K

LENGTH	COLOR TEMP.	POWER	LUMENS	CODE
L900	4000 K	2 x 15 W	2 x 985 lm	EXT19063-40K
	3000 K	2 x 15 W	2 x 930 lm	EXT19063-30K

3000K 4000K 5000K 6500K

DIMENSION



base: L148 x W108

NOTES

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on May 20, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.