



FT



## CANNON 3

### TECHNICAL DATA



	100-264 Vac	IP66	IK08	CRI >80	CREE XP-G3 LED	<b>DALI/0-10V</b> <i>Optional</i>
---	-------------	------	------	---------	----------------	--------------------------------------

Discreet and compact aesthetically designed architectural outdoor spotlight in two body sizes, ideal for accent lighting, with 3 high power CREE LEDs, die-cast aluminium body, stainless steel screws, 6mm toughened glass, flexibility in lighting effect, extremely narrow to wide beam options, highly reliable, suitable for a variety of mounting applications including ground, wall, tree, sign and architectural accents, integral driver, easy installation, optional model in 30W / 60W also available.

**DRIVER**  
CC, 1400mA, 32Vdc


Lighting Control

Standard ☐ 1-10V ☐ DALI

CRI

Standard  
☐ CRI >80 ☐ CRI >90

BEAM ANGLE



FINISH

Grey - RAL9023 (GY)

#### TECHNICAL DATA

LED	: CREE XP-G3
System Power	: 15 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 97 lm/W (@4000K)
Lifetime	: L <sub>70</sub> B <sub>50</sub> 50,000Hrs, Ta@35°C
UGR	: <23

#### GENERAL

Mounting	: Surface mounted, Pole mounted, Spike, Outdoor
Housing	: ADC12 Die-cast aluminium
Lens	: PMMA
Diffuser	: Tempered glass
Adjustability	: Yes
Driver Mounting	: Integrated
Emergency kit	: Not Available

IP Rating	: IP66
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -20° to 60°C
Glow-wire test	: 960°
Weight	: 2.50 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 6000K



[www.switch-made.com](http://www.switch-made.com)

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

# CANNON 3

## TECHNICAL DATA




### CANNON 3



COLOR TEMP.	LED QTY.	POWER	LUMENS	CODE
2700K	3 pcs.	15 W	1369 lm	EXT04122-27K
3000K			1401 lm	EXT04122-30K
4000K			1457 lm	EXT04122-40K


2700K 3000K 4000K 5000K 6000K

### DIMENSION




### MOUNTING OPTION

#### CANNON 3 POLE



#### CANNON 3 SPIKE




#### CANNON 3 BRACKET-B




(Pole dia: 67 - 325mm, T > 4)

#### CANNON 3 BRACKET-A



#### CANNON 3 BELT



(Pole dia: 168 - 268mm)

### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT  
LUMINAIRE REF.  
QUANTITY  
DATE

Contact Name  
Mobile  
Email

www.switch-made.com

Updated on April 14, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.