



FT »

CANNON 1 RGBW

TECHNICAL DATA



	100-264 Vac	IP66	24Vdc (RGBW)	IK08	CREE XM-L LED
---	-------------	------	--------------	------	---------------

Discreet and compact aesthetically designed architectural outdoor spotlight in two body sizes, ideal for accent lighting, with single high power LED, die-cast aluminium body, stainless steel screws, 6mm toughened glass, flexibility in lighting effect, extremely narrow to wide beam options, highly reliable, suitable for a variety of mounting applications including ground, wall, tree, sign and architectural accents, integral driver, easy installation.


DRIVER
CV, 24Vdc

Lighting Control
Standard

LED

RGBW 4 in 1

BEAM ANGLE



FINISH

Grey - RAL9023 (GY)

TECHNICAL DATA

LED	: CREE XM-L
System Power	: 8 W
MacAdam Step	: SDCM <3
LED Qty.	: 1 Pcs.
Lifetime	: $L_{70} B_{50}$ 50,000Hrs, Ta@35°C
UGR	: <23

GENERAL

Mounting	: Surface mounted, Pole mounted, Spike, Outdoor
Housing	: ADC12 Die-cast aluminium
Lens	: PMMA
Diffuser	: Tempered glass
Adjustability	: Yes
Driver Mounting	: Remote
Emergency kit	: Not Available

IP Rating	: IP66
IK Rating	: IK08
Protection Class IEC	: III
Energy Class	: A++
Working Temp.	: -20° to 60°C
Glow-wire test	: 960°
Weight	: 1.80 Kg
Warranty	: 3 yrs (extendable to 5 yrs)


CANNON 1 RGBW



COLOR	LED QTY.	POWER	CODE
RGBW	1 pcs. RGBW 4 in 1	8 W	EXT04128-RGBW


2700K 3000K 4000K 5000K 6000K

DIMENSION




MOUNTING OPTION

CANNON 1 RGBW SPIKE



CANNON 1 RGBW BELT



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT
LUMINAIRE REF.
QUANTITY
DATE

Contact Name
Mobile
Email