



FT



CANNON 3 RGBW

TECHNICAL DATA



| | | | | | | | | | |
|---|-------------|------|--------------|------|---------|------|--------|---------------|---------------------|
|  | 100-264 Vac | IP66 | 24Vdc (RGBW) | IK08 | CRI >80 | RGBW | DMX512 | CREE XM-L LED | DALI/0-10V Optional |
|---|-------------|------|--------------|------|---------|------|--------|---------------|---------------------|

Discreet and compact aesthetically designed architectural outdoor spotlight in two body sizes, ideal for accent lighting, with 3 high power CREE LEDs, die-cast aluminium body, stainless steel screws, 6mm toughened glass, flexibility in lighting effect, extremely narrow to wide beam options, highly reliable, suitable for a variety of mounting applications including ground, wall, tree, sign and architectural accents, optional RGBW versions, integral driver, easy installation.

| | |
|---------------------------|---|
| DRIVER CC, 900mA, 2Vdc | Lighting Control Standard <input type="checkbox"/> 1-10V <input type="checkbox"/> DALI <input type="checkbox"/> |
| CRI | Standard <input type="checkbox"/> CRI >80 <input type="checkbox"/> CRI >90 <input type="checkbox"/> |
| BEAM ANGLE |     |
| FINISH | Grey - RAL9023 (GY)  |

TECHNICAL DATA

| | |
|--------------------|--|
| LED | : CREE XM-L |
| System Power | : 12 W |
| MacAdam Step | : SDCM <4 |
| Luminaire Efficacy | : - |
| Lifetime | : L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C |
| UGR | : <24 |

GENERAL

| | |
|-----------------|---|
| Mounting | : Surface mounted, Pole mounted, Spike, Outdoor |
| Housing | : ADC12 Die-cast aluminium |
| Lens | : PMMA |
| Diffuser | : Tempered glass |
| Adjustability | : Yes |
| Driver Mounting | : Integrated |
| Emergency kit | : Not Available |

| | |
|----------------------|-------------------------------|
| IP Rating | : IP66 |
| IK Rating | : IK08 |
| Protection Class IEC | : III |
| Energy Class | : A++ |
| Working Temp. | : -20° to 55°C |
| Glow-wire test | : 960° |
| Weight | : 2.50 Kg |
| Warranty | : 3 yrs (extendable to 5 yrs) |

2700K 3000K 4000K 5000K 6000K


CANNON 3 RGBW



| COLOR | LED QTY. | POWER | CODE |
|-------|-----------------------|-------|---------------|
| RGBW | 3 pcs. RGBW 4 in 1 | 12 W | EXT04124-RGBW |


2700K 3000K 4000K 5000K 6000K

DIMENSION




MOUNTING OPTION


CANNON 3 RGBW POLE




CANNON 3 RGBW BRACKET




CANNON 3 RGBW SPIKE



CANNON 3 RGBW POLE 2



CANNON 3 RGBW BELT



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT
LUMINAIRE REF.
QUANTITY
DATE

Contact Name
Mobile
Email