



FT




## CARA 20

### TECHNICAL DATA



	220-240 Vac	IP67	IK08	CREE LED	304 STAINLESS STEEL
---	----------------	------	------	-------------	------------------------

Ground recessed up-light, versatile choice of wattage on CARA for highlighting facades in a functional way, solid construction, good choice of selection with multiple diameters, lumen packages and beam options, excellent consistency of light color, aluminium die-cast body, tempered safety glass, 316 stainless steel ring, high grade of impact and slipping resistance, delivered with plastic recessed pot.

DRIVER	Lighting Control Standard
CRI	Standard CRI >85 CRI >90
BEAM ANGLE	
FINISH	Grey (GY) Black (BK)

#### TECHNICAL DATA

LED	: CREE LED
System Power	: 20 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 94 lm/W (@6000K)
Lifetime	: L <sub>80</sub> B <sub>10</sub> 50,000Hrs, Ta@25°C
UGR	: -

#### GENERAL

Mounting	: Ground recessed, Outdoor
Housing	: Extruded aluminium body
Heatsink	: Aluminium
Diffuser	: Toughened glass
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP67
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A+
Working Temp.	: -20° to 55°C
Glow-wire test	: 650°
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 6000K



[www.switch-made.com](http://www.switch-made.com)

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.



FT



# CARA 20

## TECHNICAL DATA




CARA 20



COLOR TEMP.	POWER	LUMENS	CODE
3000K	20 W	1600 lm	EXT02094-30K
4000K		1700 lm	EXT02094-40K
6000K		1880 lm	EXT02094-60K

**2700K 3000K 4000K 5000K 6000K**

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

**CE RoHS**

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

  
[www.switch-made.com](http://www.switch-made.com)

Updated on April 22, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.