



FT





CHROME 35-R

TECHNICAL DATA



	220-240V 50-60Hz	IP54	100 lm/W	CITIZEN 1208 LED	CRI >80/>90/>97	DIMMABLE DALI/1-10V <i>Optional</i>
---	---------------------	------	----------	---------------------	--------------------	--

Round LED deep recessed downlight, highly diverse lumen levels, elegant optical design, housing made of machined aluminium with sand white/black powder-coated finishing, passive extruded aluminium heatsink ensuring better heat dissipation, high reflection ratio aluminium reflector, durable and robust structure, SDCM<2, consistent color stability, dimmable versions available, various beam angle choices.

DRIVER CC, 800mA, 35VDC	Standard	Lighting Control Phase Dim. 1-10V DALI
CRI	CRI >80	Standard CRI >90 CRI >97
BEAM ANGLE	 30°	 60°

TECHNICAL DATA

LED	: CITIZEN 1208 LED
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 100 lm/W (@4000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <19

GENERAL

Mounting	: Ceiling recessed, Indoor
Housing	: Die-cast aluminium
Reflector	: Aluminium
Diffuser	: Clear glass
Adjustability	: No
Driver mounting	: Remote
Emergency kit	: Optional

IP Rating	: IP54
IK Rating	: IK04
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 960°C
Weight	: 1.1 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

FT »

CHROME 35-R

TECHNICAL DATA

CHROME 35-R



COLOR TEMP.	POWER	CRI	LUMENS	CODE
2700K	35 W	90+	3200 lm	INT05032-27K
3000K			3350 lm	INT05032-30K
4000K			3500 lm	INT05032-40K


2700K 3000K 4000K 5000K

FINISH

White(WH) Grey(GY) Black (BK)



DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	