




FT





CHROME 8-R

TECHNICAL DATA



| | | | | | |
|---|---------------------|------|----------|--------------------|---|
|  | 220-240V 50-60Hz | IP43 | 100 lm/W | CRI >80/>90/>97 | DIMMABLE DALI/1-10V Optional |
|---|---------------------|------|----------|--------------------|---|

Round LED deep recessed downlight, highly diverse lumen levels, elegant optical design, housing made of machined aluminium with sand white/black powder-coated finishing, passive extruded aluminium heatsink ensuring better heat dissipation, high reflection ratio aluminium reflector, durable and robust structure, SDCM<2, consistent color stability, dimmable versions available, various beam angle choices.

| | | |
|------------------------------|---|---|
| DRIVER CC, 350mA, 17.8Vdc | Standard | Lighting Control Phase Dim. 1-10V DALI |
| CRI | Standard CRI >80 | CRI >90 CRI >97 |
| BEAM ANGLE |  30° |  38° |

TECHNICAL DATA

| | |
|--------------------|--|
| LED | : BRIDGELUX V8 LED |
| MacAdam Step | : <3 SDCM |
| Luminaire Efficacy | : 91 lm/W (@4000K) |
| Lifetime | : L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C |
| UGR | : <19 |

GENERAL

| | |
|----------------------|-------------------------------|
| Mounting | : Ceiling recessed, Indoor |
| Housing | : Die-cast aluminium |
| Reflector | : Aluminium |
| Diffuser | : Clear glass |
| Adjustability | : Yes |
| Driver mounting | : Remote |
| Emergency kit | : Optional |
| IP Rating | : IP43 |
| IK Rating | : IK04 |
| Protection Class IEC | : II |
| Energy Class | : A+ |
| Working Temp. | : -20° to 50°C |
| Glow-wire test | : 960°C |
| Weight | : 0.34 Kg |
| Warranty | : 3 yrs (extendable to 5 yrs) |

FT »

CHROME 8-R

TECHNICAL DATA

CHROME 8-R



| COLOR TEMP. | POWER | CRI | LUMENS | CODE |
|-------------|-------|-----|--------|--------------|
| 2700K | 8 W | 80+ | 620 lm | INT05021-27K |
| 3000K | | | 680 lm | INT05021-30K |
| 4000K | | | 730 lm | INT05021-40K |


2700K 3000K 4000K 5000K

FINISH

White(WH) Grey(GY) Black(BK)



DIMENSION



ADJUSTABILITY

TILTABLE



FIXED



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT
LUMINAIRE REF.
QUANTITY
DATE

Contact Name
Mobile
Email