



Daylight
Sensor



Microwave
Sensor



Emergency
Control

FT



COMET PC-OPEN 1200

TECHNICAL DATA



	220-240 Vac	IP65	IK08	CRI >80	SMD 2835	110 lm/W	DIMMABLE 0-10V/DALI Optional
--	----------------	------	------	------------	----------	----------	------------------------------------

Robust and reliable weatherproof luminaire, highly sealed for extreme weather conditions, multi-functional lighting options, soft uniform lighting, high corrosion resistance, UV-stabilized opal PC diffuser, body offering IP65 protection against moisture, dust, corrosion, steel/aluminium reflector base, durable silicone rubber gasket, M20 quick-connector for fast-easy connection, stainless steel/polycarbonate clips, integrated driver, delivered with surface mounting kit and suspension hook.

DRIVER
CC, 700mA, 20-54Vdc

Lighting Control

Standard ☐ 1-10V ☐ DALI

CRI

Standard
☐ CRI >80 ☐ CRI >90

BEAM ANGLE



FINISH

White (WH)
☐

TECHNICAL DATA

LED	:	SMD 2835 LED
System Power	:	40 W
MacAdam Step	:	SDCM <3
Luminaire Efficacy	:	110 lm/W (@6500K)
Lifetime	:	$L_{80} B_{50}$ 50,000Hrs, Ta@35°C
UGR	:	<23

GENERAL

Mounting	:	Ceiling, wall mounted, suspended, industrial
Housing	:	Polycarbonate
Heatsink	:	Aluminium
Diffuser	:	Opal PC
Adjustability	:	No
Driver Mounting	:	Integrated
Emergency kit	:	3H Optional available

IP Rating	:	IP65
IK Rating	:	IK08
Protection Class IEC	:	I
Energy Class	:	A+
Working Temp.	:	-20° to 55°C
Glow-wire test	:	650°
Weight	:	1.2 Kg
Warranty	:	3 yrs (extendable to 5 yrs)

3000K 4000K 5000K 6500K

FT »

COMET PC-OPEN 1200

TECHNICAL DATA





COMET PC-OPEN 1200



COLOR TEMP.	POWER	LUMENS	CODE
3000K	40 W	4200 lm	EXT19010-30K
4000K		4320 lm	EXT19010-40K
6500K		4400 lm	EXT19010-65K

3000K 4000K 5000K 6500K

DIMENSION



Stainless steel Clip



PC Clip

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on May 9, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.