



FT




COMET PC-OPEN 600

TECHNICAL DATA



	220-240 Vac	IP65	IK08	CRI >80	SMD 2835	110 lm/W	DIMMABLE 0-10V/DALI Optional
---	-------------	------	------	---------	----------	----------	------------------------------------

Robust and reliable weatherproof luminaire, highly sealed for extreme weather conditions, multi-functional lighting options, soft uniform lighting, high corrosion resistance, UV-stabilized opal PC diffuser, body offering IP65 protection against moisture, dust, corrosion, steel/aluminium reflector base, durable silicone rubber gasket, M20 quick-connector for fast-easy connection, stainless steel/polycarbonate clips, integrated driver, delivered with surface mounting kit and suspension hook.

DRIVER CC	Lighting Control
	Standard <input type="checkbox"/> 1-10V <input type="checkbox"/> DALI <input type="checkbox"/>
CRI	Standard <input type="checkbox"/> CRI >80 <input type="checkbox"/> CRI >90 <input type="checkbox"/>
BEAM ANGLE	 120°
FINISH	White (WH) <input type="checkbox"/>

TECHNICAL DATA

LED	: SMD 2835 LED
System Power	: 20 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 110 lm/W (@6500K)
Lifetime	: L ₈₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <23

GENERAL

Mounting	: Ceiling, wall mounted, suspended, industrial
Housing	: Polycarbonate
Heatsink	: Aluminium
Diffuser	: Opal PC
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: 3H Optional available

IP Rating	: IP65
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A+
Working Temp.	: -20° to 55°C
Glow-wire test	: 650°
Weight	: 0.8 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K 6500K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.


COMET PC - OPEN 600



COLOR TEMP.	POWER	LUMENS	CODE
3000K	20 W	2100 lm	EXT19009-30K
4000K		2160 lm	EXT19009-40K
6500K		2260 lm	EXT19009-65K

3000K 4000K 5000K 6500K

DIMENSION



CLIP OPTIONS



Stainless steel Clip



PC Clip

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT
LUMINAIRE REF.
QUANTITY
DATE

Contact Name
Mobile
Email