



FT




COMET PC-OPEN 1500

TECHNICAL DATA



	220-240 Vac	IP65	IK08	CRI >80	SMD 2835	110 lm/W	DIMMABLE 0-10V/DALI Optional
---	----------------	------	------	------------	----------	----------	---

Robust and reliable weatherproof luminaire, highly sealed for extreme weather conditions, multi-functional lighting options, soft uniform lighting, high corrosion resistance, UV-stabilized opal PC diffuser, body offering IP65 protection against moisture, dust, corrosion, steel/aluminium reflector base, durable silicone rubber gasket, M20 quick-connector for fast-easy connection, stainless steel/polycarbonate clips, integrated driver, delivered with surface mounting kit and suspension hook.

DRIVER CC	Lighting Control
	Standard <input type="checkbox"/> 1-10V <input type="checkbox"/> DALI <input type="checkbox"/>
CRI	Standard <input type="checkbox"/> CRI >80 <input type="checkbox"/> CRI >90 <input type="checkbox"/>
BEAM ANGLE	 120°
FINISH	White (WH) <input type="checkbox"/>

TECHNICAL DATA

LED	: SMD 2835 LED
System Power	: 58 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 110 lm/W (@6500K)
Lifetime	: L ₈₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <23

GENERAL

Mounting	: Ceiling, wall mounted, suspended, industrial
Housing	: Polycarbonate
Heatsink	: Aluminium
Diffuser	: Opal PC
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: 3H Optional available

IP Rating	: IP65
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A+
Working Temp.	: -20° to 55°C
Glow-wire test	: 650°
Weight	: 1.5 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K 6500K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.


COMET PC - OPEN 1500



COLOR TEMP.	POWER	LUMENS	CODE
3000K	58 W	6090 lm	EXT19011-30K
4000K		6260 lm	EXT19011-40K
6500K		6380 lm	EXT19011-65K

3000K 4000K 5000K 6500K

DIMENSION



CLIP OPTIONS



Stainless steel Clip



PC Clip

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	