



FT



COMET PC-SEALED 1500

TECHNICAL DATA



	220-240 Vac	IP65	IK08	CRI >80	SMD 2835	100 lm/W	1-10V/DALI Optional
---	----------------	------	------	------------	----------	----------	------------------------

Rigid and delicate design weatherproof luminaire without any clips, smooth linearity with ease of installation, highly sealed for extreme weather conditions, high corrosion resistance, high quality opal PC diffuser, PC body offering IP65 protection against moisture, dust, corrosion, steel reflector base, durable silicone rubber gasket, 3 pin fast-connector for fast-easy connection, integrated driver, delivered with metal surface mounting kit and pendant hook.

DRIVER
CC

Lighting Control
Standard

CRI

Standard
CRI >80 CRI >90

BEAM ANGLE



FINISH

White (WH)

TECHNICAL DATA

LED	: SMD 2835 LED
System Power	: 60 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 100 lm/W (@6500K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <23

GENERAL

Mounting	: Ceiling, wall mounted, Outdoor
Housing	: PC
Heatsink	: Aluminium
Diffuser	: Opal PC
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Optional

IP Rating	: IP65
IK Rating	: IK08
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 55°C
Glow-wire test	: 850°
Weight	: 1.20 Kg
Warranty	: 3 yrs (extendable to 5 yrs)


3000K 4000K 5000K 6500K

COMET PC - SEALED 1500

COLOR TEMP.	POWER	LUMENS	CODE
3000K	60 W	5640 lm	EXT19008-30K
4000K		5780 lm	EXT19008-40K
6500K		6000 lm	EXT19008-65K

3000K 4000K 5000K 6500K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	