




FT



CRUG 4

TECHNICAL DATA



	100-264 Vac	IP66	IK08	CRI >80	CREE XP-L LED
---	-------------	------	------	---------	---------------

Compact architectural and stylish outdoor innovative projector for variety of floodlighting applications, ideal for accent lighting, with 4 high power LEDs, high-pressure die-casting aluminium body, stainless steel screws, high strength 6mm toughened glass with 90% light transmittance, extremely narrow to wide beam options, rotationally symmetric light distribution, integrated power supply with dimmable options, optional model in 15W also available.


DRIVER
CC, 1400mA, 10Vdc

Lighting Control
Standard

CRI

Standard
CRI >80 CRI >90

BEAM ANGLE



FINISH

Grey - RAL9023 (GY)

TECHNICAL DATA

LED	: CREE XP-L LED
System Power	: 20 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 100 lm/W (@4000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <23

GENERAL

Mounting	: Surface mounted, Pole mounted, Outdoor
Housing	: ADC12 Die-cast aluminium
Lens	: PMMA
Diffuser	: Tempered glass
Adjustability	: Yes
Driver Mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP66
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -20° to 60°C
Glow-wire test	: 960°
Weight	: 1.90 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 6000K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

CRUG 4

TECHNICAL DATA







CRUG 4



COLOR TEMP.	LED QTY.	POWER	LUMENS	CODE
2700K	4 pcs.	20 W	1880 lm	EXT04118-27K
3000K			1931 lm	EXT04118-30K
4000K			2008 lm	EXT04118-40K

2700K 3000K 4000K 5000K 6000K

DIMENSION



Control Light Accessories


Honeycomb Glass

Honeycomb Grill


Round-meshed Grill

MOUNTING OPTION


CRUG 4 POLE




CRUG 4 SPIKE



CRUG 4 BRACKET-A




CRUG 4 BRACKET-B



(Pole dia: 67-325mm, T > 4)

CRUG 4 BELT



(Pole dia: 168-268mm)

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT
LUMINAIRE REF.
QUANTITY
DATE

Contact Name
Mobile
Email

www.switch-made.com

Updated on April 22, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.