



FT



CRUG 6

TECHNICAL DATA



	100-264 Vac	IP66	IK08	CRI >80	CREE XP-L LED	DALI/0-10V <i>Optional</i>
---	-------------	------	------	---------	---------------	--------------------------------------

Compact architectural and stylish outdoor innovative projector for variety of floodlighting applications, ideal for accent lighting, with 6 high power LEDs, high-pressure die-casting aluminium body, stainless steel screws, high strength 6mm toughened glass with 90% light transmittance, extremely narrow to wide beam options, rotationally symmetric light distribution, integrated power supply with dimmable options, optional model in 22W also available.

DRIVER
CC, 1400mA, 15Vdc


Lighting Control

Standard ☐ 1-10V ☐ DALI

CRI

Standard
☐ CRI >80 ☐ CRI >90

BEAM ANGLE



FINISH

Grey - RAL9023 (GY)

TECHNICAL DATA

LED	: CREE XP-L LED
System Power	: 30 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 105 lm/W (@4000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <23

GENERAL

Mounting	: Surface mounted, Pole mounted, Outdoor
Housing	: ADC12 Die-cast aluminium
Lens	: PMMA
Diffuser	: Tempered glass
Adjustability	: Yes
Driver Mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP66
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -20° to 60°C
Glow-wire test	: 960°
Weight	: 2.70 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 6000K

FT »

CRUG 6

TECHNICAL DATA







CRUG 6



COLOR TEMP.	LED QTY.	POWER	LUMENS	CODE
2700K	6 pcs.	30 W	2960 lm	EXT04114-27K
3000K			3036 lm	EXT04114-30K
4000K			3157 lm	EXT04114-40K


2700K 3000K 4000K 5000K 6000K

DIMENSION




MOUNTING OPTION


CRUG 6 POLE




CRUG 6 SPIKE



CRUG 6 BRACKET-A




CRUG 6 BRACKET-B



(Pole dia: 67-325mm, T > 4)

CRUG 6 BELT



(Pole dia: 168-268mm)

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT
LUMINAIRE REF.
QUANTITY
DATE

Contact Name
Mobile
Email

www.switch-made.com

Updated on April 22, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.