



FT



CRUG 9 RGBW

TECHNICAL DATA



100-305
Vac

IP66

IK08

RGBW

DMX512

CREE
XM-L LED

Compact architectural and stylish outdoor innovative projector for variety of floodlighting applications, ideal for accent lighting, with 9 high power LEDs, high-pressure die-casting aluminium body, stainless steel screws, high strength 6mm toughened glass with 90% light transmittance, extremely narrow to wide beam options, rotationally symmetric light distribution, integrated power supply with dimmable options, spike/pole mounting version also available.


DRIVER
CV, 36Vdc, 0-1670mA

Lighting Control
Standard

LED

RGBW 4 in 1

BEAM ANGLE



FINISH

Grey - RAL9023 (GY)

TECHNICAL DATA

LED : CREE XM-L LED
System Power : 60 W
MacAdam Step : SDCM <3
LED Qty. : 9 Pcs.
Lifetime : $L_{70} B_{50}$ 50,000Hrs, Ta@35°C
UGR : <23

GENERAL

Mounting : Surface mounted, Pole mounted, Outdoor
Housing : ADC12 Die-cast aluminium
Lens : PMMA
Diffuser : Tempered glass
Adjustability : Yes
Driver Mounting : Integrated
Emergency kit : Not available

IP Rating : IP66
IK Rating : IK08
Protection Class IEC : I
Energy Class : A++
Working Temp. : -20° to 60°C
Glow-wire test : 960°
Weight : 3.60 Kg
Warranty : 3 yrs (extendable to 5 yrs)



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

CRUG 9 RGBW

TECHNICAL DATA







CRUG 9 RGBW




COLOR	LED QTY.	POWER	CODE
RGBW	9 pcs. RGBW 4 in 1	60 W	EXT04112-RGBW

DIMENSION




MOUNTING OPTION


CRUG 9 POLE




CRUG 9 SPIKE



CRUG 9 BRACKET-A




CRUG 9 BRACKET-B



(Pole dia: 67-325mm, T > 4)

CRUG 9 BELT



(Pole dia: 168-268mm)

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT
LUMINAIRE REF.
QUANTITY
DATE

Contact Name
Mobile
Email

www.switch-made.com

Updated on April 22, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.