



FT »

## CYLI-I 15W

### TECHNICAL DATA



	200-240 Vac	IP65	IK08	CRI >80/>95	CREE COB CXA1512
-----------------------------------------------------------------------------------	-------------	------	------	-------------	------------------

Durable, high sturdiness and robust ceiling cylindrical pendant light, round ceiling base, different beam angle options, CNC extruded aluminium housing, outdoor UV resistant powder coat finishing, 316L SS screws, fire resistant silicone seal waterproof gasket, 3mm thick toughened flush glass, integrated driver, versatile choice of body finish and can be customized as per project requests, suitable for airports, exhibition centers, public areas.


DRIVER  
CC, 350mA, 32-42Vdc

Lighting Control  
Standard

CRI

Standard  
CRI >80 CRI >90 CRI >95

BEAM ANGLE



FINISH



#### TECHNICAL DATA

LED	: CREE CXA1512
System Power	: 15 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 92 lm/W (@5000K)
Lifetime	: L <sub>80</sub> B <sub>10</sub> 50,000Hrs, Ta@25°C
UGR	: -

#### GENERAL

Mounting	: Suspended, Indoor
Housing	: CNC extruded aluminium
Heatsink	: Aluminium
Diffuser	: Toughened glass (3mm thick)
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP65
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -20° to 60°C
Glow-wire test	: 650°
Weight	: 1.90 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K

FT »

# CYLI-I 15W

## TECHNICAL DATA




CYLI-I 15W



COLOR TEMP.	POWER	LUMENS	CODE
3000K	15 W	1319 lm	EXT05131-30K
4000K		1350 lm	EXT05131-40K

3000K 4000K 5000K

DIMENSION



### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	



www.switch-made.com

Updated on April 21, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.