



FT



## CYLI-II 20W

### TECHNICAL DATA



	200-240 Vac	IP65	IK08	CRI >80/>95	CREE COB CXA2520
---	----------------	------	------	----------------	---------------------

Durable, high sturdiness and robust ceiling cylindrical pendant light, round ceiling base, different beam angle options, CNC extruded aluminium housing, outdoor UV resistant powder coat finishing, 316L SS screws, fire resistant silicone seal waterproof gasket, 3mm thick toughened flush glass, integrated driver, versatile choice of body finish and can be customized as per project requests, suitable for airports, exhibition centers, public areas.


DRIVER  
CC, 500mA, 32-42Vdc

Lighting Control  
Standard

CRI

Standard  
CRI >80 CRI >90 CRI >95

BEAM ANGLE



FINISH



#### TECHNICAL DATA

LED	: CREE CXA2520
System Power	: 20 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 120 lm/W (@5000K)
Lifetime	: L <sub>80</sub> B <sub>10</sub> 50,000Hrs, Ta@25°C
UGR	: -

#### GENERAL

Mounting	: Suspended, Indoor
Housing	: CNC extruded aluminium
Heatsink	: Aluminium
Diffuser	: Toughened glass (3mm thick)
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP65
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -20° to 60°C
Glow-wire test	: 650°
Weight	: 2.90 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K

FT »

# CYLI-II 20W

## TECHNICAL DATA



CYLI - II 20W



COLOR TEMP.	POWER	LUMENS	CODE
3000K	20 W	2254 lm	EXT05137-30K
4000K		2372 lm	EXT05137-40K

3000K 4000K 5000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT  
LUMINAIRE REF.  
QUANTITY  
DATE

Contact Name  
Mobile  
Email

www.switch-made.com

Updated on April 15, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.