



FT



## DECK 1

### TECHNICAL DATA



	350mA	IP67	IK09	CRI >85	LUMILEDS LUXEON T	24Vdc Model (Optional)
---	-------	------	------	---------	-------------------	------------------------

Mini recessed luminaire for floor/ground/wall installation, perfect choice for accent spot lighting solutions, glare-free lighting, superior visual comfort with the baffle and honeycomb structure, good range of beam options, no heat build-up at the light beam, without any visible screws, stainless steel body, tempered safety glass, 316L stainless steel ring, corrosion resistant, low voltage constant current power supply (350mA), optional model in 24Vdc also available.

DRIVER CC, 350mA, 3Vdc	Lighting Control Standard <input type="checkbox"/> Phase Dim. <input type="checkbox"/> DALI <input type="checkbox"/>
CRI	Standard <input type="checkbox"/> CRI >85 <input type="checkbox"/> CRI >90 <input type="checkbox"/>
BEAM ANGLE	
FINISH	White (WH) <input type="checkbox"/> Grey (GY) <input type="checkbox"/> Black (BK) <input type="checkbox"/>

#### TECHNICAL DATA

LED	: LUMILEDS LUXEON T
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 76 lm/W (@4000K)
Lifetime	: L <sub>70</sub> B <sub>50</sub> 50,000Hrs, Ta@35°C
UGR	: <15

#### GENERAL

Mounting	: Ground recessed, Outdoor
Housing	: Stainless steel
Reflector	: Aluminium
Diffuser	: Toughened glass
Adjustability	: No
Driver mounting	: Remote
Emergency kit	: Not available
IP Rating	: IP67
IK Rating	: IK09
Protection Class IEC	: III
Energy Class	: A++
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 0.169 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K

FT »

# DECK 1

## TECHNICAL DATA




DECK 1



COLOR TEMP.	POWER	LUMENS	CODE
2700K	1 W	50 lm	EXT02230-27K
3000K		68 lm	EXT02230-30K
4000K		76 lm	EXT02230-40K

2700K 3000K 4000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 15, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.