



FT



DECK 7

TECHNICAL DATA



	350mA	IP67	IK09	CRI >85	CITIZEN LED	24Vdc Model (Optional)	350mA CC Remote Driver
---	-------	------	------	---------	-------------	------------------------	------------------------

Mini recessed luminaire for floor/ground/wall and ceiling installation, perfect choice for accent spot lighting solutions, glare-free lighting, superior visual comfort with the baffle and honeycomb structure, good range of beam options, no heat build-up at the light beam, without any visible screws, stainless steel body, tempered safety glass, 316L stainless steel ring, corrosion resistant, low voltage constant current power supply (350mA), optional model in 24Vdc also available.

DRIVER CC, 350mA, 19Vdc	Lighting Control Standard <input type="checkbox"/> Phase Dim. <input type="checkbox"/> DALI <input type="checkbox"/>
CRI	Standard <input type="checkbox"/> CRI >85 <input type="checkbox"/> CRI >90 <input type="checkbox"/>
BEAM ANGLE	 24°  36°  60°
FINISH	White (WH) <input type="checkbox"/> Grey (GY) <input type="checkbox"/> Black (BK) <input type="checkbox"/>

TECHNICAL DATA

LED	: CITIZEN LED
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 75 lm/W (@4000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <15

GENERAL

Mounting	: Ground recessed, Outdoor
Housing	: Stainless steel
Reflector	: Aluminium
Diffuser	: Toughened glass
Adjustability	: No
Driver mounting	: Remote
Emergency kit	: Not available
IP Rating	: IP67
IK Rating	: IK09
Protection Class IEC	: III
Energy Class	: A
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 0.386 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K

FT



DECK 7

TECHNICAL DATA


DECK 7



COLOR TEMP.	POWER	LUMENS	CODE
2700K	7 W	490 lm	EXT02236-27K
3000K		502 lm	EXT02236-30K
4000K		527 lm	EXT02236-40K

2700K 3000K 4000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	