



FT »


# DELTA 12

## TECHNICAL DATA



	220-240 Vac	IP67	IK09	CRI >80	CREE LED
---	-------------	------	------	---------	----------

Discreet, sleek and ultra-thin innovative linear recessed flush mounting luminaire for floor/ground/wall and ceiling installation, designed to enhance architectural features and facades, ultimate control of glare, available in two different width and lengths, 316L SS outer trim, 8mm thick step tempered glass, die-casting aluminum radiator with powder coating, achieve the products superior adhesion and corrosion resistance, static load resistance of 2000Kg, optional 24Vdc models also available.

DRIVER	Lighting Control Standard
CRI	Standard CRI >80      CRI >90
BEAM ANGLE	L-Lens      F-Frosted 
FINISH	SS Finish 

### TECHNICAL DATA

LED	: CREE LED
System Power	: 12 W
MacAdam Step	: SDCM <4
Luminaire Efficacy	: 85 lm/W (@4000K)
Lifetime	: L <sub>70</sub> B <sub>50</sub> 50,000Hrs, Ta@35°C
UGR	: -

### GENERAL

Mounting	: Ground recessed, Outdoor
Housing	: 316 Stainless Steel
Diffuser	: Tempered glass 8mm
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not Available

IP Rating	: IP67
IK Rating	: IK09
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -40° to 60°C
Glow-wire test	: 960°
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 6500K



[www.switch-made.com](http://www.switch-made.com)

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

# DELTA 12

## TECHNICAL DATA




### DELTA 12



COLOR TEMP.	POWER	LUMENS	CODE
3000K	6 x 2 W	980 lm	EXT07205-30K
4000K		1020 lm	EXT07205-40K

2700K 3000K 4000K 5000K 6500K

#### DIMENSION



#### DIFFUSER



#### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 25, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.