

FT



ECLIPSE SUSPENDED 400

TECHNICAL DATA



	200-240 Vac	IP40	UGR 19	IK06	CRI >80	DIMMABLE TRIAC
---	-------------	------	--------	------	---------	----------------

Creative hollow shaped design which provide a strong sense of space, the curved light direction emphasizes target object in a smooth and dramatic atmosphere, revealing an unexpected art inspiration design, high visual comfort, consistent color stability, high quality of light with homogenous light, rotatable buckle on the base to make installation easier and faster, integrity to have it in suspended or surface mounted options.

DRIVER
CC, 440mA, 65-75Vdc

Lighting Control

Standard Phase Dim.

CRI

Standard

CRI >80

CRI >90

BEAM ANGLE



FINISH

White (WH)

Grey (GY)

Black (BK)

TECHNICAL DATA

LED	: SMD 2835 LED
System Power	: 35 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 94 lm/W (@5700K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@25°C
UGR	: <19

GENERAL

Mounting	: Suspended, Indoor
Housing	: Die-cast aluminium
Heat Sink	: Aluminium
Diffuser	: PC
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not Available

IP Rating	: IP40
IK Rating	: IK06
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -20° to 45°C
Glow-wire test	: 960°
Weight	: 1.60 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K 5700K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

ECLIPSE SUSPENDED 400

TECHNICAL DATA




ECLIPSE SUSPENDED 400



COLOR TEMP.	POWER	LUMENS	CODE
4000K	35 W	3220 lm	INT01211-40K
5700K		3290 lm	INT01211-57K

3000K 4000K 5000K 5700K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	



www.switch-made.com

Updated on April 25, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.