



FT



# ECLIPSE SURFACE MOUNTED 400

## TECHNICAL DATA



	200-240 Vac	IP40	UGR <19	IK06	CRI >80	DIMMABLE TRIAC
---	-------------	------	---------	------	---------	----------------

Creative hollow shaped design which provide a strong sense of space, the curved light direction emphasizes target object in a smooth and dramatic atmosphere, revealing an unexpected art inspiration design, high visual comfort, consistent color stability, high quality of light with homogenous light, rotatable buckle on the base to make installation easier and faster, integrity to have it in suspended or surface mounted options.

DRIVER CC, 440mA, 65-75Vdc	Lighting Control Standard <input type="checkbox"/> Phase Dim. <input type="checkbox"/>
CRI	Standard <input type="checkbox"/> CRI >80 <input type="checkbox"/> CRI >90 <input type="checkbox"/>
BEAM ANGLE	
FINISH	White (WH) <input type="checkbox"/> Grey (GY) <input type="checkbox"/> Black (BK) <input type="checkbox"/>

### TECHNICAL DATA

LED	: SMD 2835 LED
System Power	: 35 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 77 lm/W (@4000K)
Lifetime	: L <sub>80</sub> B <sub>10</sub> 50,000Hrs, Ta@25°C
UGR	: <19

### GENERAL

Mounting	: Surface mounted, Indoor
Housing	: Die-cast aluminium
Heatsink	: Aluminium
Diffuser	: PC
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not Available

IP Rating	: IP40
IK Rating	: IK06
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -20° to 45°C
Glow-wire test	: 960°
Weight	: 1.6 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K 5700K



[www.switch-made.com](http://www.switch-made.com)

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

# ECLIPSE SURFACE MOUNTED 400

## TECHNICAL DATA




### ECLIPSE SURFACE MOUNTED 400



COLOR TEMP.	POWER	LUMENS	CODE
4000K	35 W	3220 lm	INT01205-40K
5700K		3290 lm	INT01205-57K

3000K 4000K 5000K 5700K

### DIMENSION



### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 25, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.