



FT



EPSILON 20

TECHNICAL DATA



	220-240 Vac	IP20	SDCM<2	CRI >80	UGR<15	CREE COB LED
---	----------------	------	--------	------------	--------	-----------------

Slim cylindrical pendant light, anti-glare design and compact solution, suit for accent lighting and general lighting, harmonious lighting, stable performance to provide uniform and comfortable lighting level, high visual comfort, tensile aluminium body with oxidation treatment provides corrosion resistances, excellent heat dissipation ability, built-in driver, delivered with round ceiling base, optional wattages of 8W/12W/25W also available.

DRIVER | Lighting Control
Standard

CRI | Standard
CRI >80 CRI >90 CRI >95

BEAM ANGLE | 

BODY FINISH | White (WH) Black (BK)

TECHNICAL DATA

LED : CREE 1512 LED
System Power : 20 W
MacAdam Step : SDCM <2
Luminaire Efficacy : 95 lm/W (@4000K)
Lifetime : L₈₀B₁₀ 50,000Hrs, Ta@25°C
UGR : <15

GENERAL

Mounting : Suspended, Indoor
Housing : Die-cast aluminium
Heat Sink : Aluminium
Diffuser / Lens : PMMA
Adjustability : No
Driver Mounting : Built-in
Emergency kit : Not available

IP Rating : IP20
IK Rating : IK06
Protection Class IEC : II
Energy Class : A++
Working Temp. : -20° to 45°C
Glow-wire test : 750°
Weight : 1.00 Kg
Warranty : 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K

FT »

EPSILON 20

TECHNICAL DATA




EPSILON 20



COLOR TEMP.	POWER	LUMENS	CODE
2700K	20 W	1700 lm	INT07335-27K
3000K		1850 lm	INT07335-30K
4000K		1920 lm	INT07335-40K

2700K 3000K 4000K 5000K

DIMENSION



REFLECTOR FINISH (Optional)

Black
(Standard)



White



Gold



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	



www.switch-made.com

Updated on April 25, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.