



FT »

# GALAXY

## TECHNICAL DATA



	100-240 Vac	IP20	OSRAM COB LED	CRI >80/>90	100lm/W	UGR<16	DIMMABLE DALI/1-10V
---	-------------	------	---------------	-------------	---------	--------	---------------------

Innovative low glare GALAXY range is an ideal retrofit solution for traditional track lamps, which can be equipped with either 3-phase track adapter or single-phase track adapter, can be tilted lamp head is 360° horizontally and 90° vertically, overlapping of two slim cubes give the light more flexibility and creativity, optics designed for narrow, medium, wide beam and planar distribution for wall washer options, also can be wall washer application, optional surface mounting accessory.

DRIVER CC, 560mA, 48Vdc	Lighting Control Standard <input type="checkbox"/> Phase Dim. <input type="checkbox"/> 1-10V <input type="checkbox"/> DALI <input type="checkbox"/>
CRI	Standard <input type="checkbox"/> CRI >80 <input type="checkbox"/> CRI >90 <input type="checkbox"/> CRI >97 <input type="checkbox"/>
BEAM ANGLE	
FINISH	<input type="checkbox"/> White (WH) <input type="checkbox"/> Grey (GY) <input type="checkbox"/> Black (BK)

### TECHNICAL DATA

LED : OSRAM GW CSSRM2  
 MacAdam Step : <3 SDCM  
 Luminaire Efficacy : 100 lm/W (@4000K)  
 Lifetime : L<sub>70</sub>B<sub>50</sub> 50,000Hrs, Ta@35°C  
 UGR : <16

### GENERAL

Mounting : 3C 4wire track mounting, Indoor  
 Housing : Die-cast aluminium  
 Reflector : PC  
 Diffuser : PMMA  
 Adjustability : Yes  
 Driver mounting : Integrated  
 Emergency kit : Not available

IP Rating : IP20  
 IK Rating : IK06  
 Protection Class IEC : II  
 Energy Class : A+  
 Working Temp. : -20° to 50°C  
 Glow-wire test : 650°C  
 Weight : 1.3 Kg  
 Warranty : 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K



FT »

# GALAXY


## TECHNICAL DATA



COLOR TEMP.	POWER	LUMENS	CODE
2700K	30 W	2730 lm	INT03020-27K
3000K		2880 lm	INT03020-30K
4000K		3000 lm	INT03020-40K

2700K 3000K 4000K 5000K

DIMENSION



Optimized passive cooling system



Intelligent joint can hold at any point



Built-in dimmer (1-10V dimming)

NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 15, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.