



FT



HUBI-II A

TECHNICAL DATA



	220-240 Vac	IP65	IK07	CRI >80/>95	CREE XP-E LED
---	----------------	------	------	----------------	------------------

LED wall mounted luminaire with round and oval shaped bulkhead with different frame design, uniformly diffused ambient lighting, vandal resistant design, optimum visual comfort in extreme weather conditions, high powered CREE LED chips, die-cast aluminium housing, outdoor UV resistant powder coat finish, 316L stainless steel screws, integrated driver, fire-resistant silicone seal waterproof gasket, 2mm thick PMMA diffuser, optional rectangular shaped model also available.

DRIVER
CC, 350mA, 32-42Vdc

Lighting Control
Standard

CRI

Standard
CRI >80 CRI >90

BEAM ANGLE



FINISH

Grey
RAL9006 (GY) Black
RAL9005 (BK)

TECHNICAL DATA

LED	: CREE XP-E
System Power	: 15 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 87 lm/W (@5000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: -

GENERAL

Mounting	: Surface mounted, Outdoor
Housing	: Die-cast Aluminium
Heatsink	: Aluminium
Diffuser	: PMMA (2mm thick)
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP65
IK Rating	: IK07
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -20° to 60°C
Glow-wire test	: 650°
Weight	: 2.00 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

HUBI-II A

TECHNICAL DATA




HUBI-II A



COLOR TEMP.	POWER	LUMENS	CODE
3000K	15 W	1200 lm	EXT06085-30K
4000K		1275 lm	EXT06085-40K
5000K		1300 lm	EXT06085-50K


3000K 4000K 5000K

DIMENSION





OPTIONAL

HUBI-II B



HUBI-II C



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	