

FT »

IOTA

TECHNICAL DATA

	220-240 Vac	IK08	CRI >80	PF >0.9	CITIZEN LED
---	----------------	------	------------	------------	----------------

Surface mounted square wall light with single or dual side illumination with functionality of changing beam angle manually, discreet and integrative design to use with architectural surroundings, glare free light and enhanced visual comfort, body made of aluminium, specially designed narrow beam optical accessory to create slim beam of light, different body color choices, ideal solution for building façade, exterior walls, entrance zones.

DRIVER
CC, 350mA, 18.2Vdc

Lighting Control
Standard

CRI

Standard
CRI >80 CRI >90

FINISH

White (WH) Grey (GY) Black (BK)

TECHNICAL DATA

LED	: CITIZEN 0603 LED
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 70 lm/W (@4000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: -

GENERAL

Mounting	: Wall mounted, Indoor, Outdoor
Housing	: Aluminium
Reflector	: Aluminium
Diffuser	: Glass
Adjustability	: No
Driver mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP54
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 0.428 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K

FT



IOTA

TECHNICAL DATA


IOTA



COLOR TEMP.	POWER	LUMENS	CODE
2700K	7 W	420 lm	INT09002-27K
3000K		455 lm	INT09002-30K
4000K		490 lm	INT09002-40K

2700K 3000K 4000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT

LUMINAIRE REF.

QUANTITY

DATE

Contact Name

Mobile

Email