



FT »

IROUND-X

TECHNICAL DATA

	220-240 Vac	IP65	CRI >80	PF >0.9
-----------------------------------------------------------------------------------	-------------	------	---------	---------

Wall recessed luminaire for functional or directional lighting, can be used for indoor or outdoor applications, maintenance-free, ideal for applications such as lighting walkways and stairways, die-cast aluminum housing with corrosion-resistant paint, polycarbonate lens protects the LED from moisture, dirt and other contaminants, advanced sense of style delivers maximum durability and functionality, provides long lasting performance in many wet location applications, integrated driver.

DRIVER	Lighting Control Standard
CRI	Standard CRI >80
BEAM ANGLE	 120°
FINISH	White (WH) Grey (GY) Black (BK)

TECHNICAL DATA

LED	: SMD LED
System Power	: 1.2 W
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 67 lm/W (@4000K)
Lifetime	: L ₈₀ B ₁₀ 100,000Hrs, Ta@35°C
UGR	: <14

GENERAL

Mounting	: Wall recessed, Outdoor
Housing	: Die-cast aluminium
Reflector	: Aluminium
Diffuser	: Tempered glass
Adjustability	: No
Driver Mounting	: Integrated
Emergency kit	: NA
IP Rating	: IP65
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A+
Working Temp.	: -20° to 55°C
Glow-wire test	: 850°C, 5 sec
Weight	: -
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K

FT »

IROUND-X

TECHNICAL DATA




IROUND-X



COLOR TEMP.	POWER	LUMENS	CODE
3000K	1.2 W	80 lm	INT03071-30K

2700K 3000K 4000K 5000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	

Contact Name	
Mobile	
Email	



www.switch-made.com

Updated on April 15, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.