



FT



## JUPY-X 10

### TECHNICAL DATA



	220-240 Vac	IP44	IK04	CRI >80	COB LED	DIMMABLE 1-10V/DALI
---	----------------	------	------	------------	---------	------------------------

Modular designed LED downlight, homogenous basic and general lighting with precise light distribution, low glare rating, equipped with excellent luminous performing COB LED, high visual comfort, body made of aluminium, clear glass diffuser with minimal wattage consumption, best quality-performance and price positioning, efficient LED replacement for downlights with compact florescent lamps, remote driver, also available in 15W (dia 140mm) model.

DRIVER  
CC, 250mA, 25-42Vdc

Lighting Control  
Standard ☐ Phase Dim. ☐ 1-10V ☐ DALI ☐

CRI

Standard  
☐ CRI >80 ☐ CRI >90

BEAM ANGLE



FINISH

White (WH) ☐ Black (BK) ☐

#### TECHNICAL DATA

LED	: COB LED
Macadam Step	: SDCM <2
Luminaire Efficacy	: 105 lm/W (@5000K)
Lifetime	: L <sub>70</sub> B <sub>50</sub> 50,000Hrs, Ta@35°C
UGR	: <25

#### GENERAL

Mounting	: Ceiling recessed, Indoor
Housing	: Aluminium
Reflector	: Aluminium
Diffuser	: Clear glass
Adjustability	: No
Driver Mounting	: Remote
Emergency kit	: Optional

IP Rating	: IP44
IK Rating	: IK04
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 750°
Weight	: 0.22 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K

FT »

# JUPY-X 10

## TECHNICAL DATA




JUPY-X 10



COLOR TEMP.	POWER	LUMENS	CODE
3000K	10 W	855 lm	INT05148-30K
4000K		953 lm	INT05148-40K
5000K		1050 lm	INT05148-50K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	