



FT



JUPY-X 30

TECHNICAL DATA



	220-240 Vac	IP44	IK04	CRI >80	COB LED	DIMMABLE 1-10V/DALI
---	-------------	------	------	---------	---------	---------------------

Modular designed LED downlight, homogenous basic and general lighting with precise light distribution, low glare rating, equipped with excellent luminous performing COB LED, high visual comfort, body made of aluminium, clear glass diffuser with minimal wattage consumption, best quality-performance and price positioning, efficient LED replacement for downlights with compact florescent lamps, remote driver, also available in 15W (dia 140mm) model.

DRIVER
CC, 700mA, 25-42Vdc

Lighting Control
Standard ☐ Phase Dim. ☐ 1-10V ☐ DALI ☐

CRI

Standard ☐ CRI >80 ☐ CRI >90 ☐

BEAM ANGLE



FINISH

White (WH) ☐ Black (BK) ☐

TECHNICAL DATA

LED	: COB LED
Macadam Step	: SDCM <2
Luminaire Efficacy	: 103 lm/W (@5000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: <25

GENERAL

Mounting	: Ceiling recessed, Indoor
Housing	: Aluminium
Reflector	: Aluminium
Diffuser	: Clear glass
Adjustability	: No
Driver Mounting	: Remote
Emergency kit	: Optional

IP Rating	: IP44
IK Rating	: IK04
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 750°
Weight	: 0.72 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K

FT »

JUPY-X 30

TECHNICAL DATA




JUPY-X 30



COLOR TEMP.	POWER	LUMENS	CODE
3000K	30 W	2800 lm	INT05154-30K
4000K		2970 lm	INT05154-40K
5000K		3080 lm	INT05154-50K

2700K 3000K 4000K 5000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 15, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.