



FT



KIKEX 9

TECHNICAL DATA



	220-240 Vac	IP65	IK08	CREE XP-E LED	24Vdc Model (Optional)
---	----------------	------	------	------------------	----------------------------------

Small and elegantly designed projector light, compact structure, accent spotlight solution, perfect and precise light distribution, flexibility in terms of combining multiple units with the specially designed bracket, superior aluminium alloy body offering high heat dissipation, tempered glass, narrow light optical technology, LED engine adopts high power chip, wall and ceiling mounted installation, integrated driver, optional monocolour/RGB version also available.

DRIVER

Lighting Control
Standard

CRI

Standard
CRI >80 CRI >90

BEAM ANGLE

 25°

FINISH

Grey (GY) Black (BK)

TECHNICAL DATA

LED : CREE SMD LED
System Power : 18 W
MacAdam Step : SDCM <3
Luminaire Efficacy : 100 lm/W (@4000K)
Lifetime : L₈₀ B₁₀ 50,000Hrs, Ta@35°C
LED Qty. : 9 pcs.

GENERAL

Mounting : Surface mounted, Outdoor
Housing : Die-cast aluminium
Heat Sink : Aluminium
Diffuser : PMMA
Adjustability : Yes
Driver Mounting : Inbuilt
Emergency kit : Not available

IP Rating : IP65
IK Rating : IK08
Protection Class IEC : I
Energy Class : A+
Working Temp. : -20° to 55°C
Glow-wire test : 750°
Weight : 0.77 Kg
Warranty : 3 yrs (extendable to 5 yrs)

3000K 4000K 6000K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

KIKEX 9

TECHNICAL DATA




KIKEX 9



COLOR TEMP.	LED QTY.	POWER	LUMENS	CODE
2700K	9 pcs.	18 W	1690 lm	EXT04211-27K
3000K			1728 lm	EXT04211-30K
4000K			1800 lm	EXT04211-40K

3000K 4000K 6000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 25, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.