



FT »

# KOOKI 50

## TECHNICAL DATA



	100-240 Vac	IP65	IK08	PF >0.9	90 lm/W	CRI >80	SMD 2835 LED
---	-------------	------	------	---------	---------	---------	--------------

Mini curve shaped LED floodlight, ideal solution for area lighting and general illumination, ultra-thin and very compact design, available in different wattage and sizes, higher price-quality ratio, IP rated glands, better heat dissipation with inner honey comb structure, aluminum alloy die-cast body, toughened glass diffuser, high quality polycarbonate lens, easy to install and mount, optional sensor models, delivered with 0.3m cable, driver on-board (built-in).

DRIVER	Lighting Control Standard
CRI	Standard CRI >80
BEAM ANGLE	 120°
FINISH	White (WH)    Black (BK)  

### TECHNICAL DATA

LED	: SMD 2835 LED
System Power	: 50 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 90 lm/W (@4000K)
Lifetime	: L <sub>80</sub> B <sub>10</sub> 50,000Hrs, Ta@35°C
UGR	: -

### GENERAL

Mounting	: Surface mounted, Spike, Outdoor
Housing	: Die-cast aluminium
Lens	: PC
Diffuser	: Tempered glass
Adjustability	: Yes
Driver Mounting	: Built-in
Emergency kit	: NA

IP Rating	: IP65
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A+
Working Temp.	: -20° to 55°C
Glow-wire test	: 960°
Weight	: 2.00 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 6000K

FT »

# KOOKI 50

## TECHNICAL DATA




### KOOKI 50



COLOR TEMP.	POWER	LUMENS	CODE
3000K	50 W	4250 lm	EXT14165-30K
4000K		4400 lm	EXT14165-40K
5000K		4500 lm	EXT14165-50K

2700K 3000K 4000K 5000K 6000K

### DIMENSION



### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	



[www.switch-made.com](http://www.switch-made.com)

Updated on April 25, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.