



FT



KOOKI 20

TECHNICAL DATA



	100-240 Vac	IP65	IK08	PF >0.9	90 lm/W	CRI >80	SMD 2835 LED
--	----------------	------	------	------------	------------	------------	-----------------

Mini curve shaped LED floodlight, ideal solution for area lighting and general illumination, ultra-thin and very compact design, available in different wattage and sizes, higher price-quality ratio, IP rated glands, better heat dissipation with inner honey comb structure, aluminum alloy die-cast body, toughened glass diffuser, high quality polycarbonate lens, easy to install and mount, optional sensor models, delivered with 0.3m cable, driver on-board (built-in).

DRIVER | Lighting Control
Standard

CRI | Standard
CRI >80

BEAM ANGLE | 
120°

FINISH | White (WH) Black (BK)

TECHNICAL DATA

LED : SMD 2835 LED
System Power : 20 W
MacAdam Step : SDCM <3
Luminaire Efficacy : 90 lm/W (@4000K)
Lifetime : L₈₀ B₁₀ 50,000Hrs, Ta@35°C
UGR : -

GENERAL

Mounting : Surface mounted, Spike, Outdoor
Housing : Die-cast aluminium
Lens : PC
Diffuser : Tempered glass
Adjustability : Yes
Driver Mounting : Built-in
Emergency kit : NA

IP Rating : IP65
IK Rating : IK08
Protection Class IEC : I
Energy Class : A+
Working Temp. : -20° to 55°C
Glow-wire test : 960°
Weight : 1.20 Kg
Warranty : 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 6000K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

KOOKI 20

TECHNICAL DATA




KOOKI 20



COLOR TEMP.	POWER	LUMENS	CODE
3000K	20 W	1700 lm	EXT14042-30K
4000K		1760 lm	EXT14042-40K
5000K		1800 lm	EXT14042-50K

2700K 3000K 4000K 5000K 6000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 25, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.