



FT »

KUBI 9

TECHNICAL DATA



	90-264 Vac	IP65	IK08	86 lm/W	RGB (optional)
---	------------	------	------	---------	----------------

High-contrast outdoor accent lighting solution with different size-wattage choices, 9 high power LEDs, uniform light distribution, improved optics with various light distribution patterns, die-cast aluminium body, tempered safety glass, anti-impact abrasion resistant, high heat dissipation, can be installed on ground/ceiling/wall mounted, optimal solution for outdoor architectural and landscape lighting applications, optional RGB model in 3R3G3B 18W also available, extended lower wattage range with input 24Vdc comprising 12W, 6W, 3W and 1W.

DRIVER CC, 600mA, 20-36Vdc	Lighting Control Standard <input type="checkbox"/> DALI <input type="checkbox"/>
CRI	Standard <input type="checkbox"/> CRI >80 <input type="checkbox"/> CRI >90
BEAM ANGLE	
FINISH	<input type="checkbox"/> White (WH) <input type="checkbox"/> Grey (GY) <input type="checkbox"/> Black (BK)

TECHNICAL DATA

LED	: CREE XPE
System Power	: 19 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 86 lm/W (@5000K)
Lifetime	: L ₇₀ B ₅₀ 50,000Hrs, Ta@35°C
UGR	: -

GENERAL

Mounting	: Surface mounted, Outdoor
Housing	: Die-cast aluminium
Lens	: PMMA
Diffuser	: Tempered glass
Adjustability	: Yes
Driver Mounting	: Integrated
Emergency kit	: Not available

IP Rating	: IP65
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A++
Working Temp.	: -20° to 55°C
Glow-wire test	: 850°
Weight	: 1.10 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 6000K



FT »

KUBI 9

TECHNICAL DATA




KUBI 9



COLOR TEMP.	LED QTY.	POWER	LUMENS	CODE
3000K	9 pcs.	19 W	1530 lm	EXT04207-30K
4000K			1568 lm	EXT04207-40K
6000K			1634 lm	EXT04207-60K

3000K 4000K 6000K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	