




FT »









LINE MAX 1

TECHNICAL DATA



	220-240 Vac	IP20	CRI > 80	IK08	3 SDCM	160 lm/W	DIMMABLE 1-10V/DALI Optional
---	----------------	------	-------------	------	--------	----------	------------------------------------

LED linear trunking system with wide choice of beam optics, applied to the shelving lighting in tight space such as warehouse, supermarket and workshop, polished steel profile housing, PMMA lens, PC endcaps, polycarbonate optical cover, with different lighting control options, lower maintenance, built-in driver, suspended/surface mounting choices, optional X, L, T node connectors also available.

DRIVER	Lighting Control			
	Standard	Phase Dim.	1-10V	DALI
CRI	Standard			
	CRI >80	CRI >90		
BEAM OPTICS	Standard			
	 Sharp (25°)	 Narrow (60°)	 Wide (90°)	 Flat-PC (120°)
	 Flood-Lens (120°)	 Asymmetric (right)	 Asymmetric (left)	 Double asymmetric
FINISH				
	White (WH)	Silver (SL)	Black (BK)	

TECHNICAL DATA

LED	: SMD 2835 LED
System Power	: 50 W
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 160 lm/W (@4000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@35°C

GENERAL

Mounting	: Suspended, Surface Mounted
Housing	: Steel
Lens	: PMMA
Diffuser	: PC
Adjustability	: No
Driver mounting	: Integrated
Emergency kit	: Optional

IP Rating	: IP20
IK Rating	: IK08
Protection Class IEC	: I
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 650°C
Weight	: 3.6 Kg.
Warranty	: 3 yrs (extendable to 5 yrs)

3000K 4000K 5000K 6000K

FT »

LINE MAX 1

TECHNICAL DATA



LINE MAX 1



COLOR TEMP.	LED	POWER	LUMENS	MAX. LINKABLE	CODE
4000K	243 LEDs	50 W	8000 lm	70 pcs.	INT04131-40K

3000K 4000K 5000K 6000K

DIMENSION



OPTIONAL



PC FROSTED DIFFUSER (120° Beam)



PC LENS DIFFUSER

NOTES

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	