



FT



LINY 18

TECHNICAL DATA



Optional



	220-240 Vac	IP67	IK07	CRI >80	CREE LED	24Vdc Model (Optional)	RGBW (Optional)
---	-------------	------	------	---------	----------	----------------------------------	--------------------

Higher performance linear wall washing solution with extended range of selection, novel structure without epoxy sealing, extruded aluminium body, tempered glass diffuser, stainless steel support, high heat dissipation and prolonged life span, multi-angle and polarized lens design to maximize utilization of light, flexible and adjustable bracket makes the beam angle more accurate and brings a more extraordinary grazing effect, optional baffle/visor structure for reduced glare and optimized lighting control, 24Vdc model and RGB versions are also available.


DRIVER
CV, 24 Vdc

Lighting Control
Standard

CRI

Standard
CRI >80 CRI >90

BEAM ANGLE



FINISH

Grey (GY) Black (BK)

TECHNICAL DATA

LED	: CREE LED
System Power	: 18 W
MacAdam Step	: SDCM <3
Luminaire Efficacy	: 91 lm/W (@4000K)
Lifetime	: L ₈₀ B ₁₀ 50,000Hrs, Ta@35°C
UGR	: -

GENERAL

Mounting	: Surface mounted, Outdoor
Housing	: Extruded aluminium (6063)
Heat Sink	: Aluminium
Diffuser	: Tempered glass
Adjustability	: Yes
Driver Mounting	: External
Emergency kit	: Not available

IP Rating	: IP67
IK Rating	: IK07
Protection Class IEC	: I
Energy Class	: A+
Working Temp.	: -20° to 55°C
Glow-wire test	: 750°
Weight	: 2.28 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K 6000K 6500K



www.switch-made.com

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

LINEY 18 TECHNICAL DATA




LINEY 18



COLOR TEMP.	LED QTY.	POWER	LUMENS	CODE
2700K	18 pcs.	18 W	1530 lm	EXT12031-27K
3000K			1584 lm	EXT12031-30K
4000K			1630 lm	EXT12031-40K

2700K 3000K 4000K 5000K 6000K 6500K

DIMENSION



NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT
LUMINAIRE REF.
QUANTITY
DATE

Contact Name
Mobile
Email

www.switch-made.com

Updated on April 25, 2022

All technical specifications and datas are subject to modification at any time and without notice.
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.