



FT




## MIG 3-S

### TECHNICAL DATA



	220-240V 50-60Hz	IP43	90 lm/W	CITIZEN 1004	CRI >80/>90/>97	DIMMABLE <b>DALI/1-10V</b> Optional
---	---------------------	------	---------	--------------	--------------------	---

Innovatively designed LED gimbal downlight range for accent lighting with triple trim with single lighting head, high version diversity for sophisticated lighting designs, elegant optical design, housing made of die-cast aluminium with sand white/black powder-coated finishing, passive aluminium sheet heatsink ensuring better heat dissipation, high reflection ratio aluminium reflector, durable, SDCM<2, dimmable versions available, various beam angle choices.

DRIVER CC, 250mA, 34Vdc	Lighting Control Standard <span>Phase Dim.</span> <span>1-10V</span> <span>DALI</span>
CRI	Standard <span>CRI &gt;80</span> <span>CRI &gt;90</span> <span>CRI &gt;97</span>
BEAM ANGLE	
FINISH	White (WH) <span>Black (BK)</span>

#### TECHNICAL DATA

LED	: CITIZEN 1004
MacAdam Step	: <3 SDCM
Luminaire Efficacy	: 85 lm/W (@4000K)
Lifetime	: L <sub>70</sub> B <sub>50</sub> 50,000Hrs, Ta@35°C
UGR	: <21

#### GENERAL

Mounting	: Ceiling recessed, Indoor
Housing	: Die-cast aluminium
Reflector	: Aluminium
Diffuser	: Clear glass
Adjustability	: Yes
Driver mounting	: Remote
Emergency kit	: Optional

IP Rating	: IP43
IK Rating	: IK04
Protection Class IEC	: II
Energy Class	: A+
Working Temp.	: -20° to 50°C
Glow-wire test	: 960°C
Weight	: 1.01 Kg
Warranty	: 3 yrs (extendable to 5 yrs)

2700K 3000K 4000K 5000K



FT »

# MIG 3-S

## TECHNICAL DATA




### MIG 3-S



COLOR TEMP.	POWER	CRI	LUMENS	CODE
2700K	3 x 10 W	90+	2040 lm	INT06050-27K
3000K			2280 lm	INT06050-30K
4000K			2550 lm	INT06050-40K

2700K 3000K 4000K 5000K


### DIMENSION



### OPTIC CHOICES



Code: **AG**  
Special anti-glare baffle for lower UGR



Code: **OL**  
Optic lens for more uniform lighting effect (45°)



### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	