



FT



## MUIRA-S

### TECHNICAL DATA



IP54

CRI  
>82

LUMILEDS  
LED

Wall marker recessed luminaire for functional, directional and accent lighting solution, elegant and harmonious lighting effect, asymmetric downward washlighting on the ground, compact and glare free design, high visual comfort, can be used for indoor or semi-outdoor applications, no visible screws, superior durability, aluminium body, tempered glass diffuser, drives with remote 700mA constant current remote driver, best suitable for staircase, walkway, building entrance, open areas.

DRIVER  
CC, 700mA, 3Vdc

Lighting Control

Standard

Phase Dim.

CRI

Standard

CRI >82

FINISH

White (WH)

Grey (GY)

Black (BK)

#### TECHNICAL DATA

LED	:	LUMILEDS LUXEON T
MacAdam Step	:	<3 SDCM
Luminaire Efficacy	:	71 lm/W (@4000K)
Lifetime	:	L <sub>70</sub> B <sub>50</sub> 50,000Hrs, Ta@35°C
UGR	:	-

#### GENERAL

Mounting	:	Wall recessed, Indoor, Outdoor
Housing	:	Aluminium
Reflector	:	Aluminium
Diffuser	:	Glass
Adjustability	:	No
Driver mounting	:	Remote
Emergency kit	:	Optional

IP Rating	:	IP54
IK Rating	:	IK07
Protection Class IEC	:	III
Energy Class	:	A
Working Temp.	:	-20° to 50°C
Glow-wire test	:	650°C
Weight	:	0.093 Kg
Warranty	:	3 yrs (extendable to 5 yrs)

2700K 3000K 4000K



[www.switch-made.com](http://www.switch-made.com)

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.

FT »

# MUIRA-S

## TECHNICAL DATA




### MUIRA S



COLOR TEMP.	POWER	LUMENS	CODE
2700K	2 W	120 lm	INT01516-27K
3000K		130 lm	INT01516-30K

2700K 3000K 4000K

### DIMENSION



### NOTES

ISO DOC. NO.: SM-OPN-QSF08

CE RoHS

PROJECT	
LUMINAIRE REF.	
QUANTITY	
DATE	
Contact Name	
Mobile	
Email	

www.switch-made.com

Updated on April 18, 2022

All technical specifications and datas are subject to modification at any time and without notice.  
The rated values (@ta25°C) of luminous flux and electrical load are subject to initial tolerance of +/- 10%. Tolerance of CCT are subject to +/- 150K.